



WWW.LOWE.COM

Lowe Boats | 2900 Industrial Dr. | Lebanon, MO 65536 | 417-532-9101

All specifications subject to change. Lowe Boats reserves the right to discontinue models or change specifications, materials, color or design at any time without incurring obligations. Some models are shown with optional features. All boats meet or exceed United States Coast Guard and Canada Coast Guard regulations and National Marine Manufacturers Association Certification Standards.

GS 200

LOWE
PONTOON



2012

Specifications

Length	20' / 6.1M	Log Gauge	.080" / 2.05mm
Overall Length	20' 2" / 6.15M	Max. Person Capacity	9
Beam	8' 6" / 2.5M	Max. Person Weight Capacity	1,267 lb / 575 kg
Pontoon Diameter	23" / .58m	Approx. Hull Weight	1,900 lb / 862 kg
Max HP Capacity	60 hp / 45kw	Max Weight Capacity	1,869 lb / 848 kg

FEATURES

COLORS

- White Fence, grey upholstery w/ blue accents (black bimini)
- Black Fence, grey upholstery w/ blue accents (black bimini)

CONSTRUCTION

- NMMA Certified
- 23" pontoons w/ vented chambers
- Pressure-treated plywood deck
- All stainless-steel hardware
- All aluminum motor pod
- Bow and stern mooring cleats
- 1 1/4" painted rails
- Bow (24") and Port (32") gates
- Heavy-duty bimini top w/ boot & quick disconnects

SEATING

- Rotomolded console
- 4:1 anti-feedback steering

LIGHTING

- USCG navigation lights
- Interior courtesy light on console

FURNITURE

- Stern "L" group
- 2 Bow lounges
- Rotomolded seat bases
- Helm seat w/ slider
- Round table w/ drink holders
- Tinted Windscreen



WWW.LOWE.COM

Lowe Boats | 2900 Industrial Dr. | Lebanon, MO 65536 | 417-532-9101

All specifications subject to change. Lowe Boats reserves the right to discontinue models or change specifications, materials, color or design at any time without incurring obligations. Some models are shown with optional features. All boats meet or exceed United States Coast Guard and Canadian Coast Guard regulations and National Marine Manufacturers Association Certification Standards.

GS 200

**LOWE
PONTOON**



2012

OPTIONS

COVERS

- Full playpen cover

ENGINE

- Mercury 25 EL (4-Stroke)
- Mercury 25 ELPT (4-Stroke)
- Mercury 40 ELPT (4-Stroke)
- Mercury 40 ELPT BF (4-Stroke)
- Mercury 50 ELPT (4-Stroke)
- Mercury 50 ELPT BF (4-Stroke)
- Mercury 60 ELPT (4-Stroke)
- Mercury 60 ELPT BF (4-Stroke)

TRAILER

- Painted tandem trailer
- Painted tandem trailer w/ Aluminum Mag Wheels
- Galvanized tandem trailer
- Galvanized tandem Vinyl Bunk trailer
- Painted tandem trailer w/ disc brakes
- Galvanized tandem trailer w/ disc brakes
- Painted tandem w/ dual axle disc brakes
- Galvanized tandem w/ dual axle disc brakes
- Spare tire w/ U-bolt bracket
- Ratchet Tie Downs

MISCELLANEOUS

- Boarding ladder (portable)
- Drop-down privacy curtain
- Jensen Marine AM/FM Stereo w/ MP3 player jack & Sirius capable
- Instrument Pkg. (volt, tach and speedometer)



WWW.LOWE.COM

Lowe Boats | 2900 Industrial Dr. | Lebanon, MO 65536 | 417-532-9101

All specifications subject to change. Lowe Boats reserves the right to discontinue models or change specifications, materials, color or design at any time without incurring obligations. Some models are shown with optional features. All boats meet or exceed United States Coast Guard and Canada Coast Guard regulations and National Marine Manufacturers Association Certification Standards.

GS 202

LOWE
PONTOON



2012

Specifications

Length	20' / 6.1M	Log Gauge	.080" / 2.05mm
Overall Length	20' 2" / 6.15M	Max. Person Capacity	9
Beam	8' 6" / 2.5M	Max. Person Weight Capacity	1,267 lb / 575 kg
Pontoon Diameter	23" / .58m	Approx. Hull Weight	1,900 lb / 862 kg
Max HP Capacity	60 hp / 45kw	Max Weight Capacity	1,869 lb / 848 kg

FEATURES

COLORS

- White Fence, grey upholstery w/ blue accents (black bimini)
- Black Fence, grey upholstery w/ blue accents (black bimini)

CONSTRUCTION

- NMMA Certified
- 23" pontoons w/ vented chambers
- Pressure-treated plywood deck
- All stainless-steel hardware
- All aluminum motor pod
- Bow and stern mooring cleats
- 1 1/4" painted rails
- Bow (24") and Port (32") gates
- Heavy-duty bimini top w/ boot & quick disconnects

FISHING

- 19 Gal aerated livewell w/ 2 cup holders on lid

SEATING

- Rotomolded console
- 4:1 anti-feedback steering

LIGHTING

- USCG navigation lights
- Interior courtesy light on console

FURNITURE

- Stern "L" group
- 2 Bow lounges
- Rotomolded seat bases
- Flip/Flop Helm seat w/ storage
- 3 Pedestal fishing seats
- Round table w/ drink holders
- Tinted Windscreen



WWW.LOWE.COM

Low e Boats | 2900 Industrial Dr. | Lebanon, MO 65536 | 417-532-9101

All specifications subject to change. Lowe Boats reserves the right to discontinue models or change specifications, materials, color or design at any time without incurring obligations. Some models are shown with optional features. All boats meet or exceed United States Coast Guard and Canadian Coast Guard regulations and National Marine Manufacturers Association Certification Standards.

GS 202

**LOWE
PONTOON**



2012

OPTIONS

COVERS

- Full playpen cover

ENGINE

- Mercury 25 EL (4-Stroke)
- Mercury 25 ELPT (4-Stroke)
- Mercury 40 ELPT (4-Stroke)
- Mercury 40 ELPT BF (4-Stroke)
- Mercury 50 ELPT (4-Stroke)
- Mercury 50 ELPT BF (4-Stroke)
- Mercury 60 ELPT (4-Stroke)
- Mercury 60 ELPT BF (4-Stroke)

TRAILER

- Painted tandem trailer
- Painted tandem trailer w/ Aluminum Mag Wheels
- Galvanized tandem trailer
- Galvanized tandem vinyl bunk trailer
- Painted tandem trailer w/ disc brakes
- Galvanized tandem trailer w/ disc brakes
- Painted tandem w/ dual axle disc brakes
- Galvanized tandem w/ dual axle disc brakes
- Spare tire w/ U-bolt bracket
- Ratchet Tie Downs

MISCELLANEOUS

- W55 MotorGuide Wireless (48", 55#, 12V) trolling motor w/ quick disconnect and Lowrance X50DS fishfinder w/ 4" screen, dual beam sonar w/ temp., 1000 ft. max depth, 188 watts RMS
- Vinyl floor (tan)
- Trolling motor outlet (12V) w/ harness
- Boarding ladder (portable)
- Drop-down privacy curtain
- Jensen Marine AM/FM Stereo w/ MP3 player jack & Sirius capable
- Triple tube rod holder mounted on stern livewell
- Instrument Pkg. (volt, tach and speedometer)